

PT30 Omura

Mobile Computer



Features

◆ Powerful scanning performance.

With the PT30 Omura, you can count on a high performance 1D/2D scan engine. The scan engine is patented by Newland and delivers fast and accurate scanning of a wide variety of barcodes.

◆ Excellent value for money.

This affordable mobile computer gives you the features you need for everyday use. It runs on Microsoft Windows CE.NET 6.0 and has a PXA310 806MHz CPU. Armed with 256MB RAM and 4GB flash memory, the device provides the power to support the most demanding applications.

◆ Reliable wireless connectivity.

With 802.11 b/g Wifi and Bluetooth, The PT30 Omura provides your workforce with the mobility and connection they need to work fast and fuss-free.

◆ Extended battery life.

The PT30 Omura is equipped with a 3500mAh battery that provides up to 11 hours of life on the go.

◆ Ergonomic and durable design.

The ergonomic design of the PT30 Omura optimizes single-handed use and brings all day comfort to your operations. With a 1.2 drop rating the device keeps on working despite inevitable drops and bumps, while a sealing of IP54 protects it from dust and moisture.

◆ Current models released.

PT3050-3A: Linear Imager + Wifi.

PT3050-2A: 2D area Imager + Wifi.

Application Scenarios

Suitable for indoor applications - warehouse management, retail management, food traceability, distributor management, manufacturing management, electricity meter reading, inventory counting and more.

PT30 Omura

Mobile Computer

Performance	Processor		Marvell XScale PXA310, 806MHz CPU	
	Operating System		Microsoft Windows CE.NET 6.0	
	Memory	256MB RAM		
		128MB ROM		
			4GB flash memory for user storage	
Interface		Mini USB 2.0, supports USB charging		
Physical	Dimensions		189.5 (L) ×76(W) ×45(H) mm (7.5 x 3 x 1.7 inch)	
	Weight		382g (including battery)	
	Display		2.83" QVGA with backlight TFT Touch screen LCD	
	Keypad		30 keys with backlight	
	Notification		Vibrator, speaker and multi-color LEDs	
	Battery	Main	3.7V, 3500mAh rechargeable Li-Polymer battery	
		Backup	3.7V, 150mAh rechargeable Li-Polymer battery (supports 50-hour data backup)	
	Expected Battery Life		11 hours	
	Expected Charge Time		3.5 hours (charge via AC adapter)	
	Expansion		MicroSD card slot	
	AC Adapter		Output: DC5V, 1.5A; Input: AC100~240V, 50~60Hz	
	Environmental	Operating Temperature		-10°C ~ 50°C (14°F ~ 122°F)
		Storage Temperature		-20°C ~ 60°C (-4°F ~ 140°F)
Humidity		5%~95% (non-condensing)		
Static Discharge		±15 kV (Air discharge), ±8 kV (Direct discharge)		
Drop		1.2m drops to concrete		
Sealing		IP54		
Barcode Scanning	1D Barcode	CCD (≥4mil) Laser (≥4mil) (optional)	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, etc.	
	2D Barcode	CMOS(≥5mil)	All 1D symbologies above, PDF417, QR Code, Data Matrix, Maxicode, Aztec, etc.	
Wireless	WLAN		802.11 b/g, security supports EAP, WEP, WPA, WPA2, 802.1X	
	WPAN		Bluetooth Class II V2.0	
Certifications		FCC Part15 Class B, CE EMC Class B, CCC		
Accessories		Battery, AC adapter, USB cable, stylus		

Specifications are subject to change without notice.

Version: V3.0

Newland EMEA
+31 (0) 345 87 00 33
info@newland-id.com

Newland D-A-CH
+49 (0) 294 298 76758
info@newland-id.de

Newland UK
+44 (0) 1442 212 020
sales@newland-id.co.uk

Newland Nordic & Baltic
+46 (0) 708 847 767
nordic@newland-id.com

Newland Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Newland France
+31 (0) 345 87 00 33
france@newland-id.com

Newland Middle East
+31 (0) 345 87 00 33
middleeast@newland-id.com

Newland South Africa
+27 (0) 11 553 8010
info@newland-id.co.za

Newland Italy
+39 (0) 342 056 2227
italy@newland-id.com

Newland Russia
+31 (0) 345 87 00 33
russia@newland-id.com