





## Frey Master



- Qualcomm<sup>®</sup> Snapdragon<sup>™</sup> 617 A53 Octa core 64-bit Processor
- 4.3" TFT-LCD COLOR
- · Capacitive touch panel with keypad
- 8.0M pixels CMOS color camera with autofocus
- Support Qualcomm Quick Charge 2.0 (USB only)









## **Frey Master FEATURES & SPECIFICATIONS**

Mamani	ANCE 1/CE ANNO FIGAL DOMAING SCRIPPERS DAM
Memory	eMCP, 16GB eMMC Flash ROM plus 2GB LPDDR3 RAM
Display and Touch Panel	• 4.3" Color TFT WVGA
	Capacitive type 5 points multi-touch touch panel with Gorilla Glass     Support finger, wet finger, glove and stylus
	Support miger, wet miger, grove and stytus     Sunlight-readable display
	One user accessible micro SD Memory slot with SDXC compliance
Expansion Slot	and software image upgrade features
	Micro USB (B type) support USB 2.0 OTG and USB charge
	Cradle connector support USB 2.0 and DC power input
	One user accessible Micro SIM slot
Wireless PAN	Bluetooth 4.1 LE     Support profile: HID, A2DP, OPP, SPP
	• 802.11a/b/g/n/ac Wireless LAN, 2.4GHz and 5GHz
Wireless LAN	Compliant with WEP, WPA and IEEE 802.11i WPA2
	Fast roaming under 100ms
	• Enterprise security
	Europe FDD LTE: B1/B3/B5/B7/B8/B20
	TDD LTE: B38/B40/B41
	WCDMA: B1/B5/B8
Wireless WAN	GSM: 900/1800
	<u>Japan</u>
	FDD LTE: B1/B3/B8/B18/B19/B26 TDD LTE: B41
	WCDM3: B1/B6//B8/B19
GPS	GPS, GLONASS
	• ISO14443-4 (Type A, Type B), ISO15693
NFC	• Mifare, Felica (ISO/IEC18092)
D Adamton	• 100~240Vac, 50/60Hz Input
Power Adapter	• 5V, 2A / 9V, 2A Output
Camera	Rear camera: 8.0M pixels CMOS color camera with autofocus
	LED flash light with torch     Ability for superior photography at a dark place
	One speaker
Audio and Voice	One receiver and dual noise-cancelling microphones
	3.5mm DIA stereo headset jack with mic. In
Sensor	Accelerometer, Light sensor, Proximity sensor, Gyroscope, E-compass
	Main Battery: 3.7V. 2300mAh Li-Ion smart battery pack
Dattami	• Main Battery: 3.7V. 3450mAh Li-Ion smart battery pack
Battery	One rechargeable RTC backup battery
	One rechargeable backup battery for battery swap
Indicator	One 2-color (green/red) LED for charger
	One 2-color (green/red) LED for information indicator
	One 3-color [green/red/yellow] LED for Logo
	One vibrator for scan or ring in indication     Audio tone indication
-	
Scanner	2D scanner
Keypad and Buttons	Hard key button (with back light) 12-key numeric(1-0/#/*) & Front-Key Side Key (Scan Key / volume key) Power key
Dimensions and Weights	Dimensions: 175 X 71.8 X 19.5 mm     Weight: < 300g (standard battery)
	weight: < July (standard battery)
Software	Android 6.0
User Environment	Operation Temperature : -20-60°C
	• Storage Temperature : -30~70°C (without battery)
	• Humidity : 10%~90% non-condensing
	Sealing : IP65     Drop : 1.5m MIL-STD 810G
	• Tumble: 0.5m tumbles for 300 cycles and 600 drops
	• ESD: +/-8KV direct discharge, +/-15KV air discharge
	• CE, NCC, BSMI, VCCI, TELEC
Pogulatory Compliance	• IEC62133 (Battery Pack), UN38.3, RoHS
Regulatory Compliance	BQB compliance
	WiFi logo compliance
LED Behavior	Charging LED Logo LED Information LED
	Charging: Red     Scan: Scan Start: Red     Miss Call: Red (Blinking, on: 100ms, off: 100ms)
	Charge full: Green     Decoder: Green (Blinking Once)     Message and Skype notice: Blue     Patters (aux Bod (Blinking on 100ms off 100ms)
	Battery low: Red (Blinking on) (Blinking, on: 100ms, off: 100ms)