ODATALOGIC MEMOR[™] 11 FAMILY OF MOBILE COMPUTERS

Optimized performance and flexibility in a market-proven design

Wi-Fi/cellular model







FLEXIBILITY TAILORED FOR YOUR WORKFORCE

The Memor 11 family is designed to provide a versatile solution for today's mobile workforce. With an up-to-date operating system and enhanced processing capabilities, this family of devices deliver superior scanning performance and all-around efficiency. Whether you require flexibility in Retail, Warehouse, Manufacturing, or Transportation & Logistic applications, the Memor 11 family is built to meet your needs. Choose between Wi-Fi only or Wi-Fi/Cellular models to always be connected within your premises or wherever you go.

RUGGED AND COMPACT DESIGN IN AN ENTERPRISE-GRADE FORM FACTOR

The market-proven, semi-rugged, and compact design of the Memor 11 follows the highly successful Memor 10 and can withstands more tumble hits than most comparable devices in the market.

ADVANCED BATTERY MANAGEMENT AND WIRELESS CHARGING

Agile performance due to its long-lasting swappable battery and embedded SafeSwap[™] Technology which ensures uninterrupted continuity. Its effective wireless charging system provides ultra-reliable contactless charging that helps reduce maintenance and promotes efficient charging.

IMPROVED SCANNING PERFORMANCE

Heighten scanning performance in dark warehouse environments with the high-end 2D scan engine, plus increased accuracy and efficiency when paired with Datalogic's exclusive 'Green Spot' Technology in scan-intensive settings.

ENTERPRISE-READY SOLUTION; A SECURE INVESTMENT

Certified as an Android[™] Enterprise Recommended device with fortified security and privacy settings of Android 11, plus the benefits of Google Mobile Services.

FEATURES

- Dedicated Wi-Fi Only and Wi-Fi/Cellular models
- Market-proven design, compact and robust
- Superior processing capabilities + 4GB of RAM
- 5-inch capacitive multi-touch HD display
- Android 11 with Google Mobile Services (upgradeable to Android 15)
- Ultra-slim 2D imager enhanced for dark environment performance + Datalogic's exclusive 'Green Spot' technology for visual good-read feedback
- Ultra-reliable swappable battery with SafeSwap™ capability and Smart Battery Management
- Contactless wireless charging helps reduce maintenance costs and promotes proper charging of the device
- Chemical resistant enclosure designed to withstand daily cleaning with harsh disinfectant solutions
- Backward compatible with all existing Memor 10 accessories
- Access to full suite of value-added Datalogic Software Applications Tools
- EASEOFCARE Service Plans and Datalogic Shield to extend lifecycle and extend years of protection on the device.





INDUSTRY - APPLICATIONS

- Retail:
 - Assisted sales
 - Inventory Management
 - Markdowns / Markups
 - Shelf Replenishment
 - Online Order Fulfillment
 - BOPIS / BORIS
 - Access control / Ticketing
 - Hospitality: Order taking
- Warehouse & Manufacturing:
 Inbound / Outbound Logistics
 - Sort, Pick, and Pack
 - Shipping / Receiving
 - Production & Quality Control
 - Inventory Management
 - Track & Trace
 - Intralogistics
- T&L:
 - Field Service / Maintenance
 - Deliveries / DSD
 - Route accounting / Order processing
 - Proof of Delivery / DamageWorkforce management

MEMOR 11 FAMILY OF MOBILE COMPUTERS TECHNICAL SPECIFICATIONS

WIRFLESS COMMUNICATIONS

WIRELESS COMMU	
Local Area Network (WLAN)	IEEE 802.11 a/b/g/n/ac and 802.11 d/h/i/k/r/v/w; Wi-Fi alliance Certification; WPA3 (Personal and Enterprise)
Personal Area Network (WPAN)	Class 2, Bluetooth® V5.0, Low Energy (BLE) Support
NFC Communication	Support for the following standards: ISO14443-4 (type-A, type-B); ISO15693; Mifare; Felica
* WWAN Cellular *Only applies to Wi-Fi/Cellular Model	LTE-Advanced / 4G+; Cat 6 • EMEA and ROW Configuration: GSM: Quad band; WCDMA: B1/5/8; FDD_LTE: B1/3/5/7/8/20/28; TDD_LTE: B38/39/40/41 • North America Configuration (PTCRB certified): GSM: Quad band; WCDMA: B1/2/4/5/8; FDD_LTE: B2/4/5/7/12/13/17/25/26/28
Global Positioning System (GPS)	Integrated Assisted-GPS (A-GPS) Supported Types: GPS, GLONASS, BeiDou
DECODING CAPABI	LITY
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
Digital Watermark Codes	Digimarc® Barcode
2D Codes	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, Dotcode
Postal Codes	Australian Post, Japan Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC), USPS Intelligent Mail
Stacked Codes	Micro-PDF417, PDF417, GS1 Composite, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, OCR (ID Cards, Passport)
ELECTRICAL	
Battery	Replaceable battery pack with rechargeable Li-Ion batteries; 3.8 V; 4,100 mAh (15.6 Watt-hours)
Wireless Charging	10 Watt fast charging
Wireless Charging ENVIRONMENTAL	
	10 Watt fast charging Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test.
ENVIRONMENTAL	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2-
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach;
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces SENSORS	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F USB-C: High Speed USB 2.0 Host and Client
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces SENSORS Vibration	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F USB-C: High Speed USB 2.0 Host and Client Software programmable for duration and intensity
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces SENSORS Vibration Magnetometer	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F USB-C: High Speed USB 2.0 Host and Client Software programmable for duration and intensity Senses orientation (eCompass)
ENVIRONMENTAL Drop Resistance Tumbles Particulate and Water Sealing Chemical Resistance Healthcare Cleanable Temperature INTERFACES Interfaces SENSORS Vibration Magnetometer Accelerometer	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/ concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test. Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2- 32 without rubber boot IP65 Chemical cleanser and industrial oil resistant Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F USB-C: High Speed USB 2.0 Host and Client Software programmable for duration and intensity Senses orientation (eCompass) 3-Axis accelerometer to detect orientation

PHYSICAL CHARACTERISTICS		
Dimensions	15.5 x 7.8 x 1.87 cm / 6.1 x 3.07 x 0.73 in	
Display	5 inch IPS HD resolution 720 x 1280; LED backlight; Touch Screen: 5 points multi-touch capacitive panel with Dragontrail hardened glass	
Keys	Physical Keys: 2 side scan keys; Power On/Off; Volume Up/ Down; 3 user programmable Android™ keys	
Weight	With Battery: 285.0 g / 10.0 oz	
READING PERFORMANCE		
Camera	Resolution: 13 megapixel; Illumination: User controllable LED flash; Lens: Auto focus	
Scan Engine	2D Ultra slim area imager (supports 1D / 2D codes); Datalogic's 'Green Spot' for good-read feedback; Halogen™ DE2102-HP: Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending on bar code density and type; Resolution: Megapixel (1280 x 800 pixels); Illumination: White and Red LEDs (for Digimarc); Aiming: 650nm VLD; Field of View: 42°H x 26°V	
Print Contrast (Minimum)	25%	
Minimum Element Width	Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils; PDF: 0.0762 mm / 3 mils; Data Matrix: 0.152 mm / 6 mils	
SAFETY & REGULATORY		
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.	
Environmental Compliance	Complies to EU RoHS	
SOFTWARE		
DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.io		
Protection	Shield - Android Security Updates, Launcher – to lockdown device to kiosk mode, Enterprise Browser - to web-browse only to a set of approved URLs, Integrity KIT - to safeguard HW interfaces	
Configuration	Scan2Deploy Studio – to configure and stage devices, OEMConfig – for UEM/EMM Compatibility, AE QR Code Enrollment – for easy EMM/UEM enrollment	
Development	SDKs (Java, Kotlin, Xamarin, .NET MAUI JavaScript), Visual Formatter – a no-code platform for barcode formatting, Wedge – a configurable bar code scanning input method	
Optimization	SoftSpot – a draggable touch scanner trigger; Logger – to collect advanced device events log; Wi-Fi Guard – to collect Wi-Fi data and statistics; Battery Manager – to select from different charging policies	
Additional Features		
Provisioning	Android Zero Touch, Android Enterprise QR code Enrolment, NFC Bump, EMM Token Enrollment, DPC Identifier Enrollment	
UEM/EMM Compatibility Highlight	SOTI Mobicontrol VMWare Workspace One, Microsoft Intune, 42Gears SureMDM, Ivanti Neurons, Ivanti Avalanche, and any DEM Config compliant UEM/EMM	
Terminal Emulator and PTT Compatibility Highlight	Ivanti Velocity, StayLinked Smart TE, Zello PTT	
SYSTEM		
Expansion Slots	Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible	
SIM Slot	MicroSIM Standard size	
Memory	System RAM: 4 GB; eMMC Flash: 32 GB	
Microprocessor	2 GHz Octa-core	
Operating System Real-Time Clock	Android v11 with GMS / AER (Upgradeable to Android 15) Time and date stamping under software control	
WARRANTY & EASE		
Warranty	1-Year Factory Warranty	
EASEOFCARE	Post-sales service programs for 3- or 5-year coverage on the device and charger	

ACCESSORIES















94A150095 Single Slot Charging Dock

94A150096 3-Slot Charging Dock

94ACC0192 4-slot Battery Charging Dock 94ACC0297 / Triple: 94ACC0288)

Ethernet Adaptors (Single:

94A150097 Vehicle 94ACC0201 Scan Charging Dock

94ACC0193 Trigger Handle Protective Boot

DLR-SLED01-EU **RFID** Reader Sled

© 2023-2024 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. • Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. • Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. • The Bluetooth word marks and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners • Product specifications are subject to change without notice. • DS-MEMOR11-EN Revision D 20240306