

HR1550 CE Wahoo

Wireless Handheld Barcode Scanner



Features

◆ Powerful scanning performance.

HR1550 CE wireless handheld barcode scanner is able to read 1D symbologies as well as PDF417 and MicroPDF417. This model adopts Zigbee technology to realize wireless communication and supports standard RS-232 / USB.

◆ Operating modes.

Data Transmission supports Synchronous, Asynchronous and Batch mode. Memory capacity for offline scanning is up to 4095 EAN-13 barcodes of 13mil.

◆ Zigbee wireless.

Zigbee technology, supporting long distance communication up to 50m & easy networking to expand coverage.

◆ Super one pair.

Cradle and scanner(s) can be paired one-to-one or one-to-many, simply via the Match key on cradle. And the cradle is also able to seek the paired scanner(s) via the Match key.

Application Scenarios

Supermarkets, shopping malls, warehouse management, retail management, food traceability, distributor management, manufacturing management, inventory counting and more.

HR1550 CE Wahoo

Wireless Handheld Barcode Scanner

Performance	Light Source	620nm Visible Red LED	
	Image Sensor	Linear imager	
	Symbologies	Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, PDF417(max. 255 bytes), MicroPDF417(max. 255 bytes), etc.	
	Reading Precision	≥4mil	
	Scan Angle	Pitch	±55°@ 0°Roll and 0° Skew
		Roll	±30°@ 0°Pitch and 0° Skew
		Skew	±75°@ 0°Roll and 0° Pitch
	Min. Symbol Contrast	15%	
	Interfaces	RS-232, USB	
	Physical	Dimensions Scanner (L×W×H)	113.5×73×159mm
Dimensions Cradle (L×W×H)		195 x 82.5 x 47 mm	
Weight		210g (including battery)	
Weight of cradle		150g	
Notification		Beep, LED indicator	
Power Adapter (optional)		Output: DC 5V, 1.5A Input: AC 100~240V, 50~60Hz	
Environmental	Operating Temperature	-10°C~50°C	
	Storage Temperature	-20°C~60°C	
	Humidity	5%~95% (non-condensing)	
	ESD	±8 KV (contact discharge); ±12 KV (air discharge)	
	Drop	1.5m	
	Sealing	IP52	
Wireless	Operating Modes	Synchronous, Asynchronous and Batch modes	
	Radio Technology	2.4 to 2.4835 GHz ISM Band, Zigbee technology	
	Communication Distance	≥50 m	
	Data Rate	20-250 KBps	
	Battery	2200mAh Li-ion Battery	
	Expected Hours of Operation	>17 hours	
	Charging Time	Around 3.5 hours for full charge	
Number of Scans	60,000 scans per charge		
Certifications	FCC Part15 Class B , CE EMC Class B		

**Test conditions: Code 39, 3 Bytes; Resolution=10mil; W:N=2.5:1; PCS=0.8; Barcode Height=40mm; Scan Distance=210mm, T=23, Illumination= 200 LUX

Specifications are subject to change without notice.

Version: V1.0.2

Newland EMEA
+31 (0) 345 87 00 33
info@newland-id.com

Newland D-A-CH
+49 (0) 294 298 76758
info@newland-id.de

Newland UK
+44 (0) 1442 212 020
sales@newland-id.co.uk

Newland Nordic & Baltic
+46 (0) 708 847 767
nordic@newland-id.com

Newland Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Newland France
+31 (0) 345 87 00 33
france@newland-id.com

Newland Middle East
+31 (0) 345 87 00 33
middleeast@newland-id.com

Newland South Africa
+27 (0) 11 553 8010
info@newland-id.co.za

Newland Italy
+39 (0) 342 056 2227
italy@newland-id.com

Newland Russia
+31 (0) 345 87 00 33
russia@newland-id.com