

# MT65 Beluga II

Portable Data Collector





## **Features**

## Rugged construction.

The rugged housing of the Beluga II is sealed to IP65 standards for protection against dust and water and withstands 1.2m drops to concrete.

## Extended battery life.

The Beluga II provides up to 10 hours of battery life on the go.

## Superior barcode reading performance.

Armed with Newland's fifth-generation of UIMG technology, the Beluga II can decode even poor quality barcodes, such as soiled or wrinkled barcodes, with ease.

## Heavily customised Android.

The value-added features of the Beluga II, including application protection and admin tools, seek to shore up Android's data security.

## **Application Scenarios**

#### Diverse functionalities.

The MT65 Beluga II offers Bluetooth/Dual band Wi-Fi 2.4GHz and 5GHz/4G/3G/ GPS/Camera functionalities to meet various application needs.

## Accessories.

For your convenience, MT65 Beluga II can be used with a pistol grip and a charging cradle.

## Current models released.

MT6550-3W (1D CCD) MT6550-4W (2D CMOS)



www.newland-id.com

Logistics, express delivery services, warehouse management, retail chains, food traceability, healthcare, distributor management, manufacturing, electricity meter reading, inventory counting.



## MT65 Beluga II

Portable Data Colletor

(	Processor Operating System	•	re 64-bit processor
	Operating System		
1		Android 5.1 (64-bit)	
	Memory	1GB RAM, 8GB ROM	
I	Interface	Micro USB 2.0, Battery charging over USB supported	
Physical [	Dimensions	166(L) ×73(W) ×26(H) mm	
<u>\</u>	Weight	330g (including battery)	
[	Display	4"WVGA (800×480) capacitive touch screen	
ł	Keypad	30 keys (side keys included) with backlight	
1	Notification	Vibrator, speaker and multi-color LEDs	
E	Battery	3.7V, 3700mAh	
E	Expected Battery Life	10 hours	
E	Expected Charge Time	4.5-5 hours (charge via AC adapter)	
(	Camera	8 megapixels, auto focus, with LED flashlight	
(	GPS	GPS	
E	Expansion	Micro SD card (max. 32GB) slot	
F	AC Adapter	Output: DC5V, 2.0A Input: AC100~240V, 50~60Hz	
Environmental <u>(</u>	Operating Temperature	-20°C to 50°C (-4°F to 122°F )	
<u> </u>	Storage Temperature	-30°C to 70°C (-22°F to 158°F)	
	Humidity	5% to 95% (non-condensing)	
<u> </u>	Static Discharge	±15 kV (Air discharge), ±8 kV (Direct discharge)	
<u> </u>	Drop	1.2m drops to concrete (for six sides, one drop per side)	
9	Sealing	IP65	
Barcode	1D Barcode	CCD (≥4mil)	Code 128, UCC/EAN-128, AIM 128, EAN-8, JAN-8, EAN-13, ISBN/
Scanning		Laser (≥4mil)	ISSN, UPC-E, UPC-A, Interleaved 25, ITF-6, ITF-14, Deutsche 14,
			Deutsche 12, COOP 25, Matrix 25, Industrial 25, Standard 25,
			Code 39, Codabar/NW7, Code 93, Code 11, Plessey, MSI/
			Plessey, GS1 Databar.
2	2D Barcode	CMOS (≥5mil) with Laser Aimer	All major 1D symbologies, PDF417, QR Code, Data Matrix, etc
RFID	13.56MHz RFID		ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693
Wireless	WLAN RADIO		IEEE 802.11 a/b/g/n, 2.4GHz and 5GHz
- N	WWAN RADIO	2G	GSM/GPRS/EDGE: B2, B3, B5, B8 (850/900/1800/1900MHz)
		3G	WCDMA(B1, B2, B5, B8); CDMA2000 1X/ EV-DO Rev. A (BC0);
			TD-SCDMA(B34, B39)
		4G	TD-LTE (B38, B39, B40, B41)
			FDD-LTE (B1, B3, B7, B20)
	WPAN RADIO		Bluetooth 4.0 LE

Accessories

\*Specifications are subject to change without notice.\*

Version: V2.0

For a complete listing of all supported barcode symbologies, please refer to the user guide.

Newland EMEA +31 (0) 345 87 00 33 info@newland-id.com

Newland France +31 (0) 345 87 00 33 france@newland-id.com

Newland D-A-CH +49 (0) 294 298 76758 info@newland-id.de

Newland Middle East +31 (0) 345 87 00 33 middleeast@newland-id.com

Newland UK +44 (0) 1442 212 020 sales@newland-id.co.uk

Newland South Africa +27 (0) 11 553 8010 info@newland-id.co.za

Newland Nordic & Baltic +46 (0) 708 847 767 nordic@newland-id.com

Newland Italy +39 (0) 342 056 2227 italy@newland-id.com

Newland Ibérica +34 (0) 93 303 74 66 info@newland-id.es

Newland Russia +31 (0) 345 87 00 33 russia@newland-id.com