

AthenaPOS

Model	L1519 (Fanless)	L1540 (Fan)	L1542 (Fan)
Processor	Intel® Celeron® J1900 (2M Cache, up to 2.42 GHz)	Intel® i3-4005U (3M Cache, 1.70 GHz)	Intel® i5-4200U (3M Cache, up to 2.60 GHz)
Memory (RAM)	DDR3L, 1 x SO-DIMM Slot	DDR3L, 2 x SO-DIMM Slot	DDR3L, 2 x SO-DIMM Slot
Storage	mSATA SSD, optional SATA SSD/HDD		
Display	15"		
Aspect Ratio	4:3		
Native (Optimal) Resolution	1024 x 768 @ 60Hz		
Touch Panel	True-flat 5-wire Resistive / Projected Capacitive		
I/O Ports	1 x USB 3.0 5 x USB 2.0 2 x COM DB9 1 x VGA 1 x HDMI 1 x LAN RJ45 1 x MIC in 3.5 mm 1 x Line out 3.5 mm 1 x 12V DC in	2 x USB 3.0 4 x USB 2.0 4 x COM DB9	2 x USB 3.0 4 x USB 2.0 4 x COM DB9
Options	MSR Built-in 2x20 VFD		
Power Supply	External 60W 12V DC, AC input voltage: 100-240 VAC, Input frequency: 50-60 Hz		
Certifications	CE, FCC, RoHS		
Gross Weight	6.60 kgs		
Packing Dimensions (W x H x D)	425 x 405 x 260mm		
Temperature	Operating: 0°C to 40°C, Storage: -20°C to 60°C		
Humidity (non-condensing)	Operating: 20% to 80%, Storage: 10% to 90%		