





XL-2000 omni- directional barcode scanner



- Large scan window, good choice for supermarket
- ◆ 20 scan lines at a rate of 1,500 scans per second
- Plug and play, not need any driver, easy operated
- ◆ 32 bit CPU, with 5 mil optical resolution
- With CE, FCC certificates
- ◆ Two years warranty.

PERFORMANCE PARAMETER

Light Source

Visible Laser Diode 650nm

Scan Pattern

20lines Omni-directional:5 flelds of 4parallellines

Scan Speed:

1500 scans/s & 75 scans/s

Print Contrast:

30%@UPC/EAN100%

Minimum Resolution:

5mil@PCS90%

Depth of Field

0-200mm for 0.33mm UPC/EAN100%

Host System Interfaces USB,RS232,Keyboard Wedge

Visual Indicators **Beeper Operation** Two color LED (blue&red)

Programmable tone&volume

UPC/EAN/JAN, UPC/EAN with supplementary,

JAN 8& JAN 13, ISBN/ISSN, EAN, Code 39,

Code 39 with full ASCII, Code 93, Code 128,

Decode Capability

Codabar (NM7), trioptic Code 39, MSI/Plessy,

GS 1 Code, Interleaved 2 of 5 (ITF), Addendum 2 of 5,

IATA Code, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, discrete 2 of 5,

Matrix 2 of 5, Code 11, UPC/EAN RSS, RSS ariants.

MECHANICAL PARAMETER

Size

LxWxH:152×78×152mm

Weight

610g

Material

ABS+PC

Cable

Standard 2M straight

ELECTRICAL PARAMETER

Voltage

5 Volts

Power

EMC

1.0 watt

Static Current

250mA

Laser Class

Meet the Grade I National Criteria for Laser Safety

CE & FCC DOC compliance ENVIRONMENTAL PARAMETER

Operating Temperature

0°C to 45°C

Storage Temperature

-20°C to 60°C

Humidity

5% to 85% relative humidity, non-condensing

Daylight, 5000Lux **Light Levels**

Shock

Designed to withstand 1.5M drops



