



XIAMEN RONGTA TECHNOLOGY CO., LTD.

ADD: No.1501 C1 Building Wanda Plaza, No.3 Jinzhong Road, Huli Area, Xiamen, Fujian, China.361006
 TEL: 0086-592-577 3715 FAX:0086-592-5659169
 MOL: 0086-18106939319 Contact Person: Jerry
 E-Mail: :rt54@rongtatech.com Web: www.rongtatech.com
 Skype: rongtatech54 Whatsapp: 0086-18059231776

Data Sheet of POS Printer RP326

Item #	Thermal Printer RP326	
Photo		
Color	Black	
Print	Printing Method	Thermal Line
	Printing Speed	250mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
Character	Character Set	ANK, GB18030 (Chinese)
	Print Font	ANK: 12 x 24, 9 x 17, Chinese: 24 x 24
	Character per Line	48-font A / 64-font B
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5 ± 0.5mm
	Paper Roll Diameter	Max: 80.0mm
	Roll Core Inner Diameter	13mm (min.)
	Paper Thickness	0.06 to 0.07mm
Paper Supply Method	Drop-in paper load	
Reliability	MCBF	60 million lines
	Auto Cutter	500,000 cuts
	TPH	100km
Barcodes	UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128	
Emulation	ESC/POS	
Driver	Windows 2000/XP/7/VISTA	
Sensor	Paper Near End Sensor, Paper End Sensor	
Drawer Port	1 Port	
Interface	RS-232, Parallel, USB, Ethernet	
Power Supply (Adapter)	AC100 ~ 240V (± 10%) DC 24V, 2A	
Auto cutter	Type	Guillotine
	Life	1,000,000 cuts
Physical	Net Weight	1.3kg
	Gross Weight	2.8kg
	Printer Dimension (WxLxH)	145 x 195 x 148 mm
Application	Restaurants, Department Stores, Kitchen, Convenience Stores, Specialty Retail, Super market	