

RP8030

Thermal Receipt Printer



- Cash drawer driver
- Support NV logo download and print
- Support auto cutter, wall mounting capable
- Kitchen and network printing are available
- Cutter stuck prevention
- Call reminder and error alarm
- Anti-losing order function



Coffee Shop



Shopping




Mart



RP8030

Thermal Receipt Printer



MODEL	RP8030		
Printing method	Direct thermal		
Printing speed	200mm/s	230mm/s	260mm/s
Interface type	USB / LAN	USB+Serial / USB+Lan	USB+Serial+Lan
Paper width	79.5±0.5mm		
Print width	72mm		
Maximum paper diameter	Φ80 mm		
Paper thickness	0.06-0.08mm		
Column capacity	576 dots/line 512 dots/line		
Line space	3.75mm(Changeable by commands)		
Commands	Compatible with ESC/POS		
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots		
Dimension	184×144×136.8mm (D×W×H)		
Gross weight	1.16 kg		
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128		
2-dimension code	//		QR CODE / PDF417
Image	Monochrome BMP image files can be load to FLASH		
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)		
Cutter	Partial		
Cutter life	1 million cuts		
Print head life	100KM		
Black Orientation	Yes		
Input buffer	64 K bytes	64 /128K bytes(USB+LAN)	128 K bytes
NV Flash	256 K bytes		
Power adaptor	AC110V/220V, 50~60Hz		
Power source	DC 24V/2.5A		
Cash drawer output	DC 24V/1A		
Work environment	Temperature: 0~45°C, humidity: 10~80RH%		
Storage environment	Temperature: -10~60°C, humidity: 10~90RH%		
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux		

