



Omnidirectional Barcode Scanner



- ⦿ Anti-scraping protection glass window
- ⦿ 32 bit CPU, with 5 mil optical resolution
- ⦿ Best choice for hypermarket, healthcare and manufacturing process control
- ⦿ Touch screen button to adjust the volume
- ⦿ 24 scan lines at a rate of 1,620 scans per second



XL-2024

Light Source	Visible Laser Diode 650nm
Scan Pattern	24 lines 6 fields of 4 parallel lines
Scan speed	1620 scans/s
Print Contrast	30% @ UPC/EAN 100%
Minimum Resolution	5mil@PCS90%
Depth of Field	0-250mm for 13 mil
Host System Interfaces	USB, RS232, Keyboard Wedge
Visual Indicators	Two color LED (blue & red)
Beeper Operation	Programmable tone & volume
Cable	Standard 2M straight

Size	L × W × H:152mm × 152mm × 75mm
Weight	576g
Material	ABS+PC
Laser Class	Meet the Grade I National Criteria for Laser Safety
Voltage	9 Volts
Static Current	430mA
EMC	CE & FCC DOC compliance
Operating Temperature	- 0°C to 45°C
Storage Temperature	- 20°C to 60°C
Humidity	5% to 95% relative humidity



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F, No.7, Kehui First Street, Science Road, Science City, Guangzhou, China
 Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com