

Omni-directional Barcode Scanner



- 54 scan lines at a rate of 3,600 scans per second
- Accurately read standard 5mil 1D codes
- Excellent reading performance on paper/commodity bar codes
- Large scan field, barcode stitching capable
- The best choice for hypermarket, healthcare, warehouse
- Support, RS-232, USB-HID, USB-VCP (virtual serial port) multiple data interfaces



Model	XL-2054	Weight	669g
Light Source	Visible Laser Diode 650nm	Input Voltage	DC 9V
Scan Pattern	54 lines	Stand-by current	500mA
Host System Interfaces	USB, RS232, Keyboard Wedge	Cable	Standard 2M straight
Beeper Operation	Programmable tone & volume	Laser Class	Meet the Grade I National Criteria for Laser Safety
Scan Speed		EMC	CE & FCC DOC compliance
Decoding Depth	0-216mm for 13mil, 0-6mm for 5mil	Interface	USB-HID, RS232, USB-VCP
Mnimum Resolution	5mil@PCS90%		0°C-45°C
Print Contrast Signal	30% @ UPC/EAN 100%		-20°C-60°C
Size	L x W x H: 152×152×75mm	Humidity	5% to 95% (non-condensing)
Case Material	ABS+PC	Light Levels	Daylight, 10000Lux
Decoding Capability	UPC/EAN/JAN, UPC/EAN with supplementary, JAN 8 & JAN 13, ISBN/ISSN, EAN, Code 39, Code 39 with full ASCII, Code 93, Code 128, Codabar (NM7), trioptic Code 39, MSI/Plessy, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, discrete 2 of 5, Matrix 2 of 5, Code 11, UPC/EAN RSS, RSS ariants.		

