









# XL-6200 Handheld Barcode Scanner

## NEW Update to 32bit CPU



- Very comfortable operating sense
- Decode most popular 1D barcodes
- Quick and fluent reading performance
- ◆ Ready for all POS system and ideal for retail
- ◆ With IP54 waterproof and dustproof protection

### PERFORMANCE PARAMETER

Light Source Visible Laser Diode 650nm

Scan Pattern Single Scan 100 times/second Scan Rate

Scan Precision 4mil

30mm@scan window, 220mm@200mm Scan Width

0-320mm (0.33mm pcs0.9) Scan Depth of field

30

65 **Elevation Angle** 

**Deflection Angle** 55 Support Inferface USB or PS/2 or RS232

Mention Pattern Buzzer, Indicator

Scan Mode Manual & continue scanning

EAN-8, EAN-13, UPC-A, UPC-E, Code 39,

30% UPC/EAN 100%

**Decode Capability** Code 128, EAN128, Codabar, Industrial 2 of 5,

Interleave 2 of 5, Matrix 2 of 5, MSI, GS1 etc.

### MECHANICAL PARAMETER

L x W x H: 175mm x 73mm x 102mm

Weight 238g ABS + PC Material

Standard 2M straight Cable

#### **ELECTRICAL PARAMETER**

5VDC Voltage

85mA peak current (120 mA) **Operating Current** 

Static Current 36mA

Meet the Grade I National Criteria for Laser Safety Laser Class

**EMC** CE & FCC DOC compliance

#### ENVIRONMENTAL PARAMETER

Operating Temperature 0°C to 45°C

Storage Temperature -20°C to 60°C

Humidity 5% to 85% relative humidity, non-condensing

Light Levels Daylight, 5000Lux

Designed to withstand 1.5M drops Shock



**Print Contrast** 

SUNLUX IOT Technology (Guangdong) Inc.

Tel:+8620-32053765

Fax:+8620-82115390

Website:www.xl-scan.com

E-mail:sales@xl-scan.com

