

# 2D Wireless Scanner



## XL-9522



- ⊙ 2200mAh large battery capacity
- ⊙ IP54 standard, withstand 1.5M drop
- ⊙ One receiver support 99 scanners
- ⊙ Read all major 1D&2D barcodes both
- ⊙ 600 meters of communication distance



Light Source	Red (LED) , White (LED)	Size	L × W × H:170mm × 71mm × 98mm
Scan Pattern	Manual & Continuous	Charge Mode	Wireless charging
Image Sensor	CMOS	Weight	900g
Working Frequency	433 MHz ISM frequency	Material	ABS+PC
Communication distance	Up to 600m at open places	Voltage	2200mAh / DC 5V
Scan Precision	4mil	Operating Current	220mA / 34mA
Scan Rate	30 times/second	Mention Pattern	Buzzer, Indicator
Scan Width	5*5cm-30*30cm	IP Standard	IP54
Depth of Scan Field	40-220mm(13mil PCS 90%)	Operate/Storage Temperature	-20°C to 60°C / -40°C to 85°C
Scan Angle	Elevation ±65° Corner360° Deflection ±60°	Humidity	5% to 90% relative humidity
Support Interface	USB-HID , USB-VCP	Shock	1.5M drops
Decoding Capability	1D : Industrial 25,standard.matrix 25, code 11, codabar,MSI, code39 (standard 39 & full ASCII code 39), code 32, code 93, code128, UPCA, UPCE, EAN13, EAN8, UPC/EAN、 add-on 2/5, ISBN, ISSN, GS1(RSS) RSS-14, LIMITED, EXPENDED, include GS1 STACK 2D : PDF417, Data Matrix ,Qr Code , ect.		



**SUNLUX IOT Technology (Guangdong) Inc.**

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: [www.xl-scan.com](http://www.xl-scan.com) E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)