

ASCII Code 39 Table

			
0	1	2	3
			
4	5	6	7
			
8	9		
			
A	B	C	D
			
E	F	G	H
			
I	J	K	L
			
M	N	O	P
			
Q	R	S	T
			
U	V	W	X
			
Y	Z		

Wireless Handheld Gun Type Scanner



Windows XP Quick Connection Guide

Version 1.00


Connecting to PC

Connect to Windows XP via SPP Master Mode

Please follow the below instructions carefully to pair the scanner with your PC.

Step. 1

Press and hold the trigger for 2 seconds to power on the scanner.





Step. 2

On your PC, go to "Control Panel"-> "Bluetooth Devices".



Step. 3

Select "Hardware" tab to view the Bluetooth address.



Step. 4

Enable Scanner SPP Master mode by scanning the following barcodes.



Start of Configuration



SPP Master Enable

Step. 5

Scan "Set wireless address" to set the Bluetooth address.



Set wireless address

Step. 6

Use the ASCII table to scan the 12 digit Bluetooth address you found in Step 3. For example: if the address is "001060AA36F8", scan "0", "0", "4", "0", "6", "0", "A", "A", "3", "6", "F", "8" from ASCII barcode labels. (or you can print out a barcode containing the full address and scan it)

Step 7

Scan "Confirm Setting" to store the address then scan "Pairing" to connect to the computer.



Confirm Setting



Pairing

Step 8

Quickly enter the PIN code on the computer. The default PIN code is "12345678". The scanner should now be connected.

Step 9

Enable COM port using a serial program (such as Hyper Terminal) to begin scanning.